

## Clamp On Current Transformers – AC



### **P32 UE 3000A / 1V**

AC sensing current transformer designed for use with the PPA range Precision Power Analyzers

#### ELECTRICAL DATA

Primary rated current	: 3000A
Measuring range	: 5A to 3600A
Frequency range	: 40Hz to 5000 Hz
Output signal	: 1A = 0.5mV
Ratio	: 2000 / 1
Accuracy	: 1% from 0.1 to 1.2 IN
Accuracy at 1000 Hz	: 500A at 1%
External mini load	: 10K Ohms
Power measurement	: Take care to keep the conventional direction P1 = S1 rear of the arrows.
Protection class	: Cat III 600 Volts according to IEC 1010-1
Dielectric strength	: 5.5 KV 50 Hz 1 min
Temperature range	: -10° to + 50° C
Operating voltage max	: 600 Volts
Opening	: Symmetrical
“Opening” cable	: Diameter 83 mm
For bus bars	: 125 x 47 mm or 100 x 58 mm
Dimensions (mm)	: 145 x 333 x 49 mm
Weight	: 1.88 Kgs
Output connection	: Cable 2 m with insulated BNC
Colour	: Blue

Designed in accordance with IEC 1010 – 1

**SAFETY WARNING:** This note must be read in full. Any operations on live conductors can be dangerous. The operator is expected to be fully aware of all necessary electrical safety regulations and procedures, taking responsibility for safe operation. Users must ensure that the equipment is at all times in its original safe conditions.

